NASA/TM-2000-209891, Vol. 202



Technical Report Series on the Boreal Ecosystem-Atmosphere Study (BOREAS)

Forrest G. Hall and Karl Huemmrich, Editors

Volume 202 BOREAS TF-7 SSA-OBS Tower Flux and Meteorological Data

E. Pattey and R.L. Desjardins

National Aeronautics and Space Administration

Goddard Space Flight Center Greenbelt, Maryland 20771

The NASA STI Program Office ... in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the lead center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- TECHNICAL PUBLICATION. Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- TECHNICAL MEMORANDUM. Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- CONTRACTOR REPORT. Scientific and technical findings by NASA-sponsored contractors and grantees.

- CONFERENCE PUBLICATION. Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- SPECIAL PUBLICATION. Scientific, technical, or historical information from NASA programs, projects, and mission, often concerned with subjects having substantial public interest.
- TECHNICAL TRANSLATION.
 English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at http://www.sti.nasa.gov/STI-homepage.html
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA Access Help Desk at (301) 621-0134
- Telephone the NASA Access Help Desk at (301) 621-0390
- Write to:
 NASA Access Help Desk
 NASA Center for AeroSpace Information
 7121 Standard Drive

Hanover, MD 21076-1320

NASA/TM-2000-209891, Vol. 202



Technical Report Series on the Boreal Ecosystem-Atmosphere Study (BOREAS)

Forrest G. Hall and Karl Huemmrich, Editors

Volume 202 BOREAS TF-7 SSA-OBS Tower Flux and Meteorological Data

Elizabeth Pattey and Raymond L. Desjardins Agriculture and Agri-Food Canada, Ottawa, Ontario

National Aeronautics and Space Administration

Goddard Space Flight Center Greenbelt, Maryland 20771

	Available from:	
NIAGA Conton for A G T C		Ni-diamater distribution of the control of the cont
NASA Center for AeroSpace Information		National Technical Information Service
7121 Standard Drive		5285 Port Royal Road
Hanover, MD 21076-1320		Springfield, VA 22161
Drice Code: A17		Del - C 1 - A 10
Price Code: A17		Price Code: A10

BOREAS TF-7 SSA-OBS Tower Flux and Meteorological Data

Elizabeth Pattey, Raymond L. Desjardins

Summary

The BOREAS TF-7 team collected meteorological data as well as energy, carbon dioxide, water vapor, methane, and nitrous oxide flux data at the BOREAS SSA-OBS site. The data were collected from 24-May to 19-Sep-1994. The data are available in tabular ASCII files.

Table of Contents

- 1) Data Set Overview
- 2) Investigator(s)
- 3) Theory of Measurements
- 4) Equipment
- 5) Data Acquisition Methods
- 6) Observations
- 7) Data Description
- 8) Data Organization
- 9) Data Manipulations
- 10) Errors
- 11) Notes
- 12) Application of the Data Set
- 13) Future Modifications and Plans
- 14) Software
- 15) Data Access
- 16) Output Products and Availability
- 17) References
- 18) Glossary of Terms
- 19) List of Acronyms
- 20) Document Information

1. Data Set Overview

1.1 Data Set Identification

BOREAS TF-07 SSA-OBS Tower Flux and Meteorological Data

1.2 Data Set Introduction

Tower-based flux of heat, momentum, H₂O, CO₂, CH₄, and N₂O were measured by eddy-correlation and/or aerodynamic gradient techniques, over the BOReal Ecosystem-Atmosphere Study (BOREAS) Southern Study Area (SSA) Old Black Spruce (OBS) stand, from day of year 144 to 155, 200 to 209, 251 to 261, in 1994.

1.3 Objective/Purpose

The purpose of this study is to determine the contribution of the boreal ecosystem to the greenhouse gas composition of the atmosphere and how this ecosystem responds to environmental conditions.

Specific objectives are the following:

- scaling-up of mass and energy surface fluxes from the local scale to the regional scale (spatial representativeness of tower-based measurements)
- quantification of the effects of ambient conditions and biological processes on gas exchanges in order to carry out a carbon budget of a black spruce stand
- determination of differences by conditional analysis of aircraft and tower data
- intercomparison between tower-based fluxes

1.4 Summary of Parameters

Latent heat flux; sensible heat flux; water vapor flux; fluxes and concentrations of carbon dioxide, methane, and nitrous oxide; momentum flux; net radiation; incident solar radiation; mean and standard deviation of wind speed and direction; friction velocity; mean U and V components of wind speed; standard deviation of the U, V, and W components of the wind speed; mean and standard deviation of specific humidity, vapor pressure, and air temperature.

1.5 Discussion

Tower Flux (TF)-07 surface fluxes were measured by micrometeorological techniques at the BOREAS SSA-OBS tower.

Momentum, CO₂, and sensible and latent heat fluxes were measured using the eddy-correlation technique (EC), while methane and nitrous oxide fluxes were measured using either EC or the aerodynamic-gradient techniques (AG). Several measurement periods of isoprene fluxes by the relaxed eddy-accumulation technique (REA) were carried out in collaboration with Dr. Hal Westberg (Trace Gas Biogeochemistry (TGB)-10).

The measurements were made at 20 m above the ground (about 12 m above the displacement plane). Wind velocities and temperature were measured with a sonic anemometer-thermometer (Kaijo-Denki DAT-310). Sensible heat flux was corrected for water vapor transfer (Schotanus et al., 1983). The sonic anemometer and the intake tubes of the closed-path analyzers were located on a boom 1.65 m long parallel to the soil surface. By rotating and/or moving the boom to one of the two ends of the south side of the tower, the sensors were oriented in the prevalent wind direction. CO₂ and H₂O concentrations were measured in fast-response absolute mode with an infrared gas analyzer (IRGA; LI-COR 6262) equipped with a 4-m-long sampling tube. The flow in the inlet was turbulent, and the signals were time adjusted to maximize the correlation with the vertical wind velocity. The CO₂ fluxes were corrected for density fluctuations associated with water vapor (Webb et al., 1980) and for sensitivity of the IRGA to water vapor, as determined in our laboratory (Pattey et al., 1992). A detailed description of the data acquisition system can be found in Pattey et al., 1995. Methane and nitrous oxide gradients between 16 and 24 m above the ground were measured with tunable diode lasers (Campbell Scientific, TGA). The eddy diffusivity coefficient, K, was calculated based on the measurements from a sonic anemometer. Isoprene fluxes were measured using REA (Pattey et al., 1993). Isoprene concentration analyses were carried out by Dr. Westberg's team (TGB-10). All the fluxes were calculated on a 30-minute basis. Measurements were carried out during the three Intensive Field Campaigns (IFCs) in 1994 between calendar days 144-155 (May-June), 200-209 (July), and 251-261 (September).

1.6 Related Data Sets

BOREAS TF-09 SSA-OBS Tower Flux, Meteorological, and Soil Temperature Data BOREAS TF-05 SSA-OJP Tower Flux and Meteorological Data BOREAS TF-03 NSA-OBS Tower Flux, Meteorological, and Soil Temperature Data BOREAS TF-04 SSA-YJP Tower Flux, Meteorological, and Soil Temperature Data BOREAS TF-11 SSA-Fen Tower Flux and Meteorological Data

2. Investigator(s)

2.1 Investigator(s) Name and Title

Dr. Raymond L. Desjardins Project Leader Air Quality Group

Dr. Elizabeth Pattey Research Scientist Air Quality Group

2.2 Title of Investigation

Areal Estimates of Mass and Energy from a Boreal Forest Biome

2.3 Contact Information

Contact 1:

Dr. Elizabeth Pattey
Centre for Land and Biological Research Resources
Agriculture and Agri-Food Canada
CEF, Bldg. 74
Ottawa, ONT. K1A 0C6
CANADA
(613) 759-1523
(613) 996-0646 (fax)
PATTEYE@GW.AGR.CA

Contact 2:

K. Fred Huemmrich University of Maryland Code 923 NASA GSFC Greenbelt, MD 20771 (301) 286-4862 (301) 286-0239 (fax) Karl.Huemmrich@gsfc.nasa.gov

3. Theory of Measurements

EC provides the most direct measurement of the flux of a gas at the land-atmosphere interface. It provides measurements of gas exchange without disturbing the environment under study and integrates the flux over a mosaic of different sources and sinks. The instantaneous transfer across a horizontal plane per unit area and per unit time is given by F = WS, where W is the vertical velocity, and S is the mixing ratio of the gas of interest. Because turbulent transfer is intermittent, it must be averaged over a certain time or distance to obtain a representative sample. The mean flux of a gas over a horizontally homogeneous surface under steady-state conditions is given by $F = \langle W'S' \rangle$, where W' and S' are the fluctuations from their mean. Reasonably stationary conditions, little horizontal advection and no chemical reaction involving the gas of interest within the air column below the measuring system are required for accurate flux measurements. These effects need to be taken into account to minimize flux divergence with height, which can lead to significant errors of surface flux estimates from aircraft-based systems (Desjardins et al., 1992).

4. Equipment

4.1 Sensor/Instrument Description

A three-axis sonic wind anemometer/thermometer from Kaijo Denki Co. (Japan) was used for measuring the fluctuations of the three wind components (U, V, W) and the temperature (T). The sonic is equipped with 90-degree probes and has a 20-cm open-path. The sonic outputs the following signals: U and V at 90°, the horizontal wind speed (U1= SQRT(U2+V2)), and theta the wind angle relative to the sonic position, in addition to W and T.

An IRGA from LI-COR, Inc., model 6262, was used for measuring water vapor and CO₂ fluctuations, equipped with a pressure transducer between the outlet of the sample cell and the pump.

A tunable-diode laser (TDL) from Campbell Scientific equipped with the laser, sample and reference detector was used for measuring CH₄ fluctuations and N₂O fluctuations.

A pyranometer from LI-COR Inc., model LI-200s was used to measure incoming solar radiation.

4.1.1 Collection Environment

Measurements were collected in intervals from late May through mid-September 1994. Over the data collection periods, the low temperatures experienced did not drop below freezing and the high temperatures were not over 27 °C.

4.1.2 Source/Platform

Above-canopy measurements were made from a 23-meter double scaffold walk-up tower.

4.1.3 Source/Platform Mission Objectives

The objectives were to measure energy and momentum fluxes and fluxes of CO₂, CH₄, and N₂O from a boreal black spruce stand and to obtain diurnal patterns of regional fluxes by combining aircraft- and tower-based flux measurements.

4.1.4 Key Variables

Sensible heat flux, latent heat flux, momentum flux, trace gas fluxes of CO₂, CH₄, and N₂O.

4.1.5 Principles of Operation

Three-axis sonic wind anemometer/thermometer from Kaijo Denki:

The ultrasonic anemometer thermometer measurement is based on the characteristics of sound waves in the atmosphere. Sound waves are propagated in air linearly at an essentially constant speed of approximately 340 m/s. Ultrasonic propagating speed in moving air, however, is slightly variable, traveling faster in a tail wind and slower in a head wind. The wind speed is deducted from the duration taken by ultrasonic pulses to travel between two ultrasonic pulse transducer elements facing each other at a fixed distance. Two ultrasonic pulse signals are alternatively emitted in opposite directions. The sound velocity in air fluctuates with temperature, as well as with humidity and atmospheric pressure. Air temperature fluctuations can be measured assuming longer pressure and humidity fluctuating cycles. In fact, humidity fluctuations should be taken into account to correct sensible heat flux as proposed by Schotanus et al. (1983).

IRGA from LI-COR:

Heteroatomic molecules are known to absorb infrared radiation at specific wavelengths; each gas has a specific absorption spectra. Radiation absorption at a given wavelength follows the Beer-Lambert Law, i.e., is a function of the path length of the measuring cell, the extinction coefficient at the specified wavelength, and the molar concentration of the heteroatomic molecule in air. The wavelength for CO₂ absorption shows sensitivity to water vapor that is attenuated by using filters. As the temperature of the cell is measured, the signals can be corrected for density fluctuations due to temperature. To be read in fast-response mode, signals should be linearized and pressure within the measuring cell included in the linearization equation.

TDL from Campbell Scientific:

The trace gas analyzer system (TGAS, Campbell Scientific) measures absolute concentrations of trace gas species by infrared absorption techniques using a TDL source. The TGAS is a fast-response closed-path analyzer, in which absorption of a specific infrared laser line by trace gas molecules (i.e. either methane or nitrous oxide) is detected. The emission lines are selected to minimize the error caused by absorption from interfering species. The laser intensity absorption follows the Beer-Lambert law of attenuation and is a function of the absorption cross-section, the path-length, and the concentration of methane or nitrous oxide molecules. In the TGAS, the laser beam absorption is measured simultaneously in a 155-cm long sample cell and in a 5-cm-long reference cell filled with either 3.05% certified methane or 0.2668% certified nitrous oxide in nitrogen maintained at about 8 kPa. The number of molecules in the sample cell is equal to the known number of molecules in the reference cell multiplied by the ratio of path-lengths between the reference and sample cell and multiplied by the ratio of the wavelength integrated absorbance between the sample and the reference cell. Both cells are maintained at low pressure to limit pressure broadening of methane or nitrous oxide absorption line. The operating temperature of the TGAS diode laser is in the range of 90 K, which is maintained with liquid nitrogen. Most TDLs are very sensitive to vibration.

Pyranometer from LI-COR:

The pyranometer is constituted of thermopiles. It is used to measure incoming solar radiation.

4.1.6 Sensor/Instrument Measurement Geometry

The sonic anemometer and the intake tubes of the closed-path analyzers were located on a boom $1.65 \, \mathrm{m}$ long, parallel to the soil surface. The boom was mounted on a rotating table to orient the sensors in the prevalent wind direction, and on a sliding carriage to access both ends of the south side of the tower. The infrared CO_2 and H_2O analyzer (IRGA; LI-COR 6262) was located on the $18.7 \, \mathrm{m}$ -high platform close to the south side of the tower. It was equipped with a 4-m sampling tube. The TDLs were located on the ground. The methane analyzer was located between the tower and the hut and had a $34.5 \, \mathrm{m}$ -long sampling tube, while the N_2O analyzer was hooked to the ceiling of the hut and had a $61.5 \, \mathrm{m}$ -long sampling tube. The conditional sampling system was located on the same platform as the IRGA. Methane and nitrous oxide gradients were measured between $16 \, \mathrm{and} \, 24 \, \mathrm{m}$ above the ground.

4.1.7 Manufacturer of Sensor/Instrument

Sonic Anemometer: Kaijo Denki Co. GENEQ, Inc. 7978 EST, rue Jarry Montreal, QUE., H1J 1H5

H2O CO2 IRGA and Pyranometer: LI-COR, Inc. P.O. Box 4425 Lincoln, NE 68504

TDL: Campbell Scientific P.O. Box 551 Logan, UT 84321

Fine-Wire Thermocouple: Campbell Scientific P.O. Box 551 Logan, UT 84321 Net Radiometer: Middleton Instruments, Inc. P.O. Box 442 South Melbourne Victoria, 3205 Australia

Data Logging System: Campbell Scientific P.O. Box 551 Logan, UT 84321

4.2 Calibration

4.2.1 Specifications

The manufacturer calibration of the LI-6262 to establish the linearization functions was done in July 1993. The field calibration of the LI-6262 was done by removing the offsets on the CO_2 and H_2O signals by passing nitrogen through the reference and sample cells, and by adjusting the gain on CO_2 channel by passing known CO_2 concentration in dry air and by passing known water vapor concentration in air to adjust the H_2O channel. The CO_2 standard was cross-referenced with BOREAS standards.

During IFC-1 and -2, a 10-liter bag was filled with ambient air and connected via a dewpoint hygrometer to the sample cell of the LI-6262. During IFC-3, the LI-610 dewpoint generator was used to produce air at known water vapor concentration.

The sonic anemometer was factory calibrated, except for the temperature, for which a linear correction function was established after IFC-3 in Ottawa against another sonic anemometer. The other signals were well calibrated.

Calibration of the TDLs: the reference cell has a known methane or nitrous oxide certified concentration flowing through it, and the signal is compensated for pressure variation, although the pressure is maintained at a steady value.

4.2.1.1 Tolerance

None given.

4.2.2 Frequency of Calibration

None given.

4.2.3 Other Calibration Information

None given.

5. Data Acquisition Methods

The signals of the instruments were collected at 20 Hz through a Labmaster board (Scientific Solutions) (analog to digital (A/D) converter) and preprocessed in real time on a microcomputer. The vertical wind speed was high-pass filtered at 0.001 Hz by a digital filter. Sums, sums of square, and sum of cross-product were accumulated over 15 seconds and saved without being converted into the proper units, so that they could be processed again if the calibration factor needed to be changed. Non-linearized signals, like those of the LI-COR 6262, were linearized in real time before being summed.

The tower had the capability to rotate to be aligned in the mean horizontal wind direction. The data acquisition and control system was able to control a fast-response valve to perform conditional sampling based on the vertical wind velocity signal. Nonmethane hydrocarbon was collected in canisters for several periods following REA (Businger and Oncley, 1990; Pattey et al., 1993).

Subcanopy signals were collected via a CR-21X (Campbell Scientific) data logger.

6. Observations

6.1 Data Notes

None.

6.2 Field Notes

None.

7. Data Description

7.1 Spatial Characteristics

7.1.1 Spatial Coverage

All data were collected at the BOREAS SSA-OBS site. North American Datum of 1983 (NAD83) coordinates for the site are latitude 53.98717° N, longitude 105.11779° W, and elevation of 628.94 m.

7.1.2 Spatial Coverage Map

Not applicable.

7.1.3 Spatial Resolution

The fluxes measured at 12 m above the displacement height integrate surface contribution, which can be described by footprint functions. The surface contributing to the flux mainly depends on the horizontal wind velocity, the wind direction, surface roughness, the atmospheric stability, and the height of measurements. The spatial coverage can be evaluated by using footprint algorithms (Schuepp et al., 1990; Horst and Weil, 1992). Flux measurements, for which the wind was blowing over a sector including the hut, the ecology tower, and/or the access path, were discarded.

7.1.4 Projection

Not applicable.

7.1.5 Grid Description

Not applicable.

7.2 Temporal Characteristics

7.2.1 Temporal Coverage

Surface flux data were collected during IFC-1 (24-May to 08-Jun), IFC-2 (19-Jul to 01-Aug), and IFC-3 (05- to 19-Sep), 1994.

7.2.2 Temporal Coverage Map

Not available.

7.2.3 Temporal Resolution

The reported data values are 30-minute averages with the reported time corresponding to the start of the sampling period.

7.3 Data Characteristics

7.3.1 Parameter/Variable

The parameters contained in the data files on the CD-ROM are:

Column Name
SITE_NAME
SUB_SITE
DATE_OBS
TIME_OBS
SENSIBLE_HEAT_FLUX_ABV_CNPY
LATENT_HEAT_FLUX_ABV_CNPY
CO2_FLUX_ABV_CNPY
CO2_CONC_ABV_CNPY
MEAN_WIND_SPEED_ABV_CNPY
SDEV_WIND_SPEED_ABV_CNPY
MEAN_WIND_DIR_ABV_CNPY
SDEV_WIND_DIR_ABV_CNPY
FRICTION_VEL_ABV_CNPY
MEAN_AIR_TEMP_ABV_CNPY
SDEV_AIR_TEMP_ABV_CNPY
DOWN_SOLAR_RAD_ABV_CNPY
MEAN_VAPOR_PRESS_ABV_CNPY
SDEV_VAPOR_PRESS_ABV_CNPY
MEAN_SPECIFIC_HUM_ABV_CNPY
SDEV_SPECIFIC_HUM_ABV_CNPY
TF07_MOMENTUM_FLUX_ABV_CNPY
MEAN_U_WIND_SPEED
MEAN_V_WIND_SPEED
SDEV_U_WIND_SPEED
SDEV_V_WIND_SPEED
SDEV_W_WIND_SPEED
H2O_FLUX_ABV_CNPY
CH4_FLUX_ABV_CNPY
CH4_CONC_ABV_CNPY
N2O_FLUX_ABV_CNPY
N2O_CONC_ABV_CNPY
CRTFCN_CODE
REVISION_DATE

7.3.2 Variable Description/DefinitionThe descriptions of the parameters contained in the data files on the CD-ROM are:

Column Name	Description			
SITE_NAME	The identifier assigned to the site by BOREAS, in the format SSS-TTT-CCCCC, where SSS identifies the portion of the study area: NSA, SSA, REG, TRN, and TTT identifies the cover type for the			
	site, 999 if unknown, and CCCCC is the identifier for site, exactly what it means will vary with site type.			
SUB_SITE	The identifier assigned to the sub-site by BOREAS, in the format GGGGG-IIIII, where GGGGG is the group associated with the sub-site instrument,			

instrument The date on which the data were collected. DATE_OBS The Greenwich Mean Time (GMT) of the start of the TIME_OBS data collection. SENSIBLE_HEAT_FLUX_ABV_CNPY The sensible heat flux measured above the canopy. LATENT_HEAT_FLUX_ABV_CNPY The latent heat flux measured above the canopy. The carbon dioxide flux measured above the canopy. CO2_FLUX_ABV_CNPY CO2_CONC_ABV_CNPY The carbon dioxide concentration measured above the canopy. The mean wind speed measured above the canopy MEAN WIND SPEED ABV CNPY over a 30 minute period. SDEV_WIND_SPEED_ABV_CNPY The standard deviation of the wind speed measured above the canopy over a 30 minute period. MEAN_WIND_DIR_ABV_CNPY The mean wind direction measured above the canopy over a 30 minute period. The standard deviation of the wind direction SDEV_WIND_DIR_ABV_CNPY measured above the canopy over a 30 minute period. FRICTION_VEL_ABV_CNPY The friction velocity above the canopy. MEAN_AIR_TEMP_ABV_CNPY The mean air temperature measured above the canopy over a 30 minute period. SDEV_AIR_TEMP_ABV_CNPY The standard deviation of the air temperature measured above the canopy over a 30 minute period. DOWN_SOLAR_RAD_ABV_CNPY The downward (incoming) solar radiation measured above the canopy. MEAN VAPOR PRESS ABV CNPY The mean vapor pressure measured above the canopy over a 30 minute period. SDEV_VAPOR_PRESS_ABV_CNPY The standard deviation of the vapor pressure measured above the canopy over a 30 minute period. The 30 minute mean specific humidity measured MEAN_SPECIFIC_HUM_ABV_CNPY above the canopy. SDEV_SPECIFIC_HUM_ABV_CNPY The 30 minute standard deviation of specific humidity measured above the canopy. TF07_MOMENTUM_FLUX_ABV_CNPY The momentum flux measured above the canopy. MEAN_U_WIND_SPEED Mean of a 30 minute period of the streamwise wind speed. MEAN_V_WIND_SPEED Mean of a 30 minute period of the lateral wind speed, perpendicular to the U wind vector. Standard deviation of the streamwise wind speed. SDEV U WIND SPEED Standard deviation of the lateral wind speed. SDEV V WIND SPEED Standard deviation of the vertical wind speed. SDEV_W_WIND_SPEED H2O_FLUX_ABV_CNPY The water vapor flux measured above the canopy. CH4_FLUX_ABV_CNPY The methane flux measured above the canopy. CH4_CONC_ABV_CNPY The methane concentration measured above the canopy. The nitrous oxide flux measured above the canopy. N2O_FLUX_ABV_CNPY N2O_CONC_ABV_CNPY The nitrous oxide concentration measured above the canopy. CRTFCN_CODE The BOREAS certification level of the data. Examples are CPI (Checked by PI), CGR (Certified by Group), PRE (Preliminary), and CPI-??? (CPI but questionable). The most recent date when the information in the REVISION DATE

e.g. HYD06 or STAFF, and IIIII is the identifier

for sub-site, often this will refer to an

referenced data base table record was revised.

7.3.3 Unit of Measurement

The measurement units for the parameters contained in the data files on the CD-ROM are:

Column Name	Units
SITE_NAME	[none]
SUB_SITE	[none]
DATE_OBS	[DD-MON-YY]
TIME_OBS	[HHMM GMT]
SENSIBLE_HEAT_FLUX_ABV_CNPY	[Watts][meter^-2]
LATENT_HEAT_FLUX_ABV_CNPY	[Watts][meter^-2]
CO2_FLUX_ABV_CNPY	[micromoles][meter^-2][second^-1]
CO2_CONC_ABV_CNPY	[parts per million]
MEAN_WIND_SPEED_ABV_CNPY	[meters][second^-1]
SDEV_WIND_SPEED_ABV_CNPY	[meters][second^-1]
MEAN_WIND_DIR_ABV_CNPY	[degrees from north]
SDEV_WIND_DIR_ABV_CNPY	[degrees from north]
FRICTION_VEL_ABV_CNPY	[meters][seconds^-1]
MEAN_AIR_TEMP_ABV_CNPY	[degrees Celsius]
SDEV_AIR_TEMP_ABV_CNPY	[degrees Celsius]
DOWN_SOLAR_RAD_ABV_CNPY	[Watts][meter^-2]
MEAN_VAPOR_PRESS_ABV_CNPY	[kiloPascals]
SDEV_VAPOR_PRESS_ABV_CNPY	[kiloPascals]
MEAN_SPECIFIC_HUM_ABV_CNPY	[grams][kilogram^-1]
SDEV_SPECIFIC_HUM_ABV_CNPY	[grams][kilogram^-1]
TF07_MOMENTUM_FLUX_ABV_CNPY	[newton][meter^-2]
MEAN_U_WIND_SPEED	[meters][second^-1]
MEAN_V_WIND_SPEED	[meters][second^-1]
SDEV_U_WIND_SPEED	[meters][second^-1]
SDEV_V_WIND_SPEED	[meters][second^-1]
SDEV_W_WIND_SPEED	[meters][second^-1]
H2O_FLUX_ABV_CNPY	<pre>[millimoles][meter^-2][second^-1]</pre>
CH4_FLUX_ABV_CNPY	[micromoles][meter^-2][second^-1]
CH4_CONC_ABV_CNPY	[parts per million]
N2O_FLUX_ABV_CNPY	[nanomoles][meter^-2][second^-1]
N2O_CONC_ABV_CNPY	[parts per million]
CRTFCN_CODE	[none]
REVISION_DATE	[DD-MON-YY]

7.3.4 Data Source

The sources of the parameter values contained in the data files on the CD-ROM are:

Column Name	Data Source
SITE_NAME	[Assigned by BORIS.]
SUB_SITE	[Assigned by BORIS.]
DATE_OBS	[Supplied by Investigator.]
TIME_OBS	[Supplied by Investigator.]
SENSIBLE_HEAT_FLUX_ABV_CNPY	[sonic anemometer]
LATENT_HEAT_FLUX_ABV_CNPY	[Infrared Gas Analyzer]
CO2_FLUX_ABV_CNPY	[Infrared Gas Analyzer]
CO2_CONC_ABV_CNPY	[Infrared Gas Analyzer]
MEAN_WIND_SPEED_ABV_CNPY	[sonic anemometer]
SDEV_WIND_SPEED_ABV_CNPY	[sonic anemometer]

MEAN_WIND_DIR_ABV_CNPY	[sonic anemometer]
SDEV_WIND_DIR_ABV_CNPY	[sonic anemometer]
FRICTION_VEL_ABV_CNPY	[sonic anemometer]
MEAN_AIR_TEMP_ABV_CNPY	[thermocouple]
SDEV_AIR_TEMP_ABV_CNPY	[thermocouple]
DOWN_SOLAR_RAD_ABV_CNPY	[Pyranometer]
MEAN_VAPOR_PRESS_ABV_CNPY	[psychrometer]
SDEV_VAPOR_PRESS_ABV_CNPY	[psychrometer]
MEAN_SPECIFIC_HUM_ABV_CNPY	[psychrometer]
SDEV_SPECIFIC_HUM_ABV_CNPY	[psychrometer]
TF07_MOMENTUM_FLUX_ABV_CNPY	[sonic anemometer]
MEAN_U_WIND_SPEED	[sonic anemometer]
MEAN_V_WIND_SPEED	[sonic anemometer]
SDEV_U_WIND_SPEED	[sonic anemometer]
SDEV_V_WIND_SPEED	[sonic anemometer]
SDEV_W_WIND_SPEED	[sonic anemometer]
H2O_FLUX_ABV_CNPY	[Infrared Gas Analyzer]
CH4_FLUX_ABV_CNPY	[tunable-diode laser]
CH4_CONC_ABV_CNPY	[tunable-diode laser]
N2O_FLUX_ABV_CNPY	[tunable-diode laser]
N2O_CONC_ABV_CNPY	[tunable-diode laser]
CRTFCN_CODE	[Assigned by BORIS.]
REVISION_DATE	[Assigned by BORIS.]

7.3.5 Data RangeThe following table gives information about the parameter values found in the data files on the CD-ROM.

Column Name	Minimum Data Value	Maximum Data Value	Missng Data Value	Unrel Data Value	Below Detect Limit	Data Not Cllctd
SITE_NAME	SSA-OBS-FLXTR	SSA-OBS-FLXTR	None	None	None	None
SUB_SITE	9TF07-FLX01	9TF07-FLX01	None	None	None	None
DATE_OBS	24-MAY-94	18-SEP-94	None	None	None	None
TIME_OBS	0	2355	None	None	None	None
SENSIBLE_HEAT_FLUX_ ABV_CNPY	-120.1	554.9	-999	None	None	None
LATENT_HEAT_FLUX_ABV _CNPY	-53.1	323.62	-999	None	None	None
CO2_FLUX_ABV_CNPY	-14.069	15.444	-999	None	None	None
CO2_CONC_ABV_CNPY	341.07	411.08	-999	None	None	None
MEAN_WIND_SPEED_ABV_ CNPY	.056	7.853	-999	None	None	None
SDEV_WIND_SPEED_ABV_ CNPY	.081	2.485	-999	None	None	None
MEAN_WIND_DIR_ABV_ CNPY	0	370.8	-999	None	None	None
SDEV_WIND_DIR_ABV_ CNPY	.05	181.154	-999	None	None	None
FRICTION_VEL_ABV_ CNPY	0	1.155	-999	None	None	None
MEAN_AIR_TEMP_ABV_ CNPY	3.85	26.59	-999	None	None	None
SDEV_AIR_TEMP_ABV_	.05	1.51	-999	None	None	None

REVISION_DATE	23-MAR-99	23-MAR-99	None	None	None	None
CRTFCN_CODE	CPI	CPI	None	None	None	None
N2O_CONC_ABV_CNPY	.258	.322	-999	None	None	None
N2O_FLUX_ABV_CNPY	-5.047	2.386	-999	None	None	None
CH4_CONC_ABV_CNPY	0	3.34	-999	None	None	None
CH4_FLUX_ABV_CNPY	-22724	99192	-999	None	None	None
H2O_FLUX_ABV_CNPY	-1.192	7.348	-999	None	None	None
SDEV_W_WIND_SPEED	.009	1.574	-999	None	None	None
SDEV_V_WIND_SPEED	.083	2.525	-999	None	None	None
SDEV_U_WIND_SPEED	.063	3.628	-999	None	None	None
MEAN_V_WIND_SPEED	-4.339	4.855	-999	None	None	None
MEAN_U_WIND_SPEED	-6.248	6.388	-999	None	None	None
ABV_CNPY						
TF07_MOMENTUM_FLUX_	-1.531	.073	-999	None	None	None
ABV CNPY						
SDEV_SPECIFIC_HUM_	.006	.746	-999	None	None	None
ABV CNPY	0.22.		223	2.0210	1.0110	1.0110
_CNP1 MEAN SPECIFIC HUM	3.217	12.407	-999	None	None	None
CNPY CNPY	.001	.114	-	ионе	MOHE	MOHE
_CNPY SDEV VAPOR PRESS ABV	0.01	111	-999	None	None	None
MEAN_VAPOR_PRESS_ABV	.501	1.882	-999	None	None	None
CNPY						
DOWN_SOLAR_RAD_ABV_	-66.36	852.52	-999	None	None	None
CNPY						

Minimum Data Value -- The minimum value found in the column.

Maximum Data Value -- The maximum value found in the column.

Missng Data Value -- The value that indicates missing data. This is used to indicate that an attempt was made to determine the parameter value, but the attempt was unsuccessful.

Unrel Data Value -- The value that indicates unreliable data. This is used to indicate an attempt was made to determine the parameter value, but the value was deemed to be unreliable by the analysis personnel.

Below Detect Limit -- The value that indicates parameter values below the instruments detection limits. This is used to indicate that an attempt was made to determine the parameter value, but the analysis personnel determined that the parameter value was below the detection limit of the instrumentation.

Data Not Cllctd -- This value indicates that no attempt was made to determine the parameter value. This usually indicates that BORIS combined several similar but not identical data sets into the same data base table but this particular science team did not measure that parameter.

Blank -- Indicates that blank spaces are used to denote that type of value. N/A -- Indicates that the value is not applicable to the respective column. None -- Indicates that no values of that sort were found in the column.

7.4 Sample Data Record

The following are wrapped versions of data records from a sample data file on the CD-ROM.

```
SITE NAME, SUB SITE, DATE OBS, TIME OBS, SENSIBLE HEAT FLUX ABV CNPY,
LATENT_HEAT_FLUX_ABV_CNPY,CO2_FLUX_ABV_CNPY,CO2_CONC_ABV_CNPY,
MEAN_WIND_SPEED_ABV_CNPY, SDEV_WIND_SPEED_ABV_CNPY, MEAN_WIND_DIR_ABV_CNPY,
SDEV_WIND_DIR_ABV_CNPY,FRICTION_VEL_ABV_CNPY,MEAN_AIR_TEMP_ABV_CNPY,
SDEV_AIR_TEMP_ABV_CNPY, DOWN_SOLAR_RAD_ABV_CNPY, MEAN_VAPOR_PRESS_ABV_CNPY,
SDEV_VAPOR_PRESS_ABV_CNPY, MEAN_SPECIFIC_HUM_ABV_CNPY, SDEV_SPECIFIC_HUM_ABV_CNPY,
TF07_MOMENTUM_FLUX_ABV_CNPY, MEAN_U_WIND_SPEED, MEAN_V_WIND_SPEED,
SDEV_U_WIND_SPEED, SDEV_V_WIND_SPEED, SDEV_W_WIND_SPEED, H2O_FLUX_ABV_CNPY,
CH4 FLUX ABV CNPY, CH4 CONC ABV CNPY, N2O FLUX ABV CNPY, N2O CONC ABV CNPY,
CRTFCN CODE, REVISION DATE
'SSA-OBS-FLXTR', '9TF07-FLX01', 01-JUN-94, 0, 129.8, 84.24, -1.976, 368.18, 1.878, 1..008,
201.8,173.501,.36,18.8,.5,432.44,.561,.019,3.648,.125,-.148,.495,1.547,.952,
1.059,.585,1.735,-999.0,-999.0,-999.0,-999.0,'CPI',23-MAR-99
'SSA-OBS-FLXTR', '9TF07-FLX01',01-JUN-94,30,23.14,43.97,-1.55,368.05,1.82,.919,
263.8,163.469,.273,18.2,.34,221.26,.575,.022,3.735,.142,-.085,.888,1.514,.708,
.836,.376,.956,-999.0,-999.0,-999.0,-999.0,'CPI',23-MAR-99
```

8. Data Organization

8.1 Data Granularity

The smallest unit of data tracked by the BOREAS Information System (BORIS) was data collected at a given site on a given date.

8.2 Data Format

The Compact Disk-Read-Only Memory (CD-ROM) files contain American Standard Code for Information Interchange (ASCII) numerical and character fields of varying length separated by commas. The character fields are enclosed with single apostrophe marks. There are no spaces between the fields.

Each data file on the CD-ROM has four header lines of Hyper-Text Markup Language (HTML) code at the top. When viewed with a Web browser, this code displays header information (data set title, location, date, acknowledgments, etc.) and a series of HTML links to associated data files and related data sets. Line 5 of each data file is a list of the column names, and line 6 and following lines contain the actual data.

9. Data Manipulations

9.1 Formulae

See Section 9.1.1.

9.1.1 Derivation Techniques and Algorithms

Momentum flux (FU; N/m²):

FU= rhoa <W'U1'>

where: W: vertical wind velocity (m/s)

U1: horizontal wind speed (m/s1)

<>: average over the averaging period

': fluctuation

rhoa: air density (g/m³)

Sensible heat flux (FT; W/m²)

$$FT = rhoa Cp < W'T' >$$

where: Cp: air specific heat at constant pressure

T: air temperature (C)

FT is corrected for humidity and velocity fluctuations (Schotanus et al., 1983)

Latent heat flux (FQ; W/m²):

$$FQ = L \text{ rhoa } MV/MA < W'NQ' > 10-3$$

where: L: coefficient of vaporization (J/g/K)

MV: molecular mass of water vapor (18 g/mol²) MA: molecular mass of dry air (29 g/mol) NQ: molar fraction (mmol H₂O/mol² dry air)

Flux of trace gases (FS; g/m²/s):

$$FS = rhoa MS/MA < W'NS' > + rhoS DF$$

where: NS: molar fraction of the species (mol S/mol² dry air)

MS: molecular mass of the species (g/mol)

rhoS: density of the species (g/m³)

DF= density fluctuation correction (Webb et al., 1980)

e species (g/mol)

rhoS: density of the species (g/m³)

DF= density fluctuation correction (Webb et al., 1980)

Expected sensitivity of trace gases to density fluctuation correction can be found in Pattey et al (1992).

For CO₂ flux measured by the LI-COR 6262, only density fluctuations due to water vapor fluctuations are involved in the correction.

9.2 Data Processing Sequence

The following steps were used to process the data:

- Collection of 15-s blocks.
- Sum over the averaging period.
- Scaling and conversion of binary data to channel units.
- Mean, standard deviation, and flux calculation.

9.2.1 Processing Steps

BORIS staff processed these data by:

- Reviewing the initial data files and loading them online for BOREAS team access.
- Designing relational data base tables to inventory and store the data.
- Loading the data into the relational data base tables.
- Working with the team to document the data set.
- Extracting the data into logical files.

9.2.2 Processing Changes

None.

9.3 Calculations

9.3.1 Special Corrections/Adjustments

None.

9.3.2 Calculated Variables

Sensible heat flux, latent heat flux, momentum flux, trace gas fluxes of CO₂, CH₄, and N₂O.

9.4 Graphs and Plots

None.

10. Errors

10.1 Sources of Error

None given.

10.2 Quality Assessment

The data were not verified against wind direction and rejection sector.

10.2.1 Data Validation by Source

None given.

10.2.2 Confidence Level/Accuracy Judgment

None given.

10.2.3 Measurement Error for Parameters

None given.

10.2.4 Additional Quality Assessments

None given.

10.2.5 Data Verification by Data Center

Data were examined to check for spikes, values that are four standard deviations from the mean, long periods of constant values, and missing data.

11. Notes

11.1 Limitations of the Data

Data were collected only during the IFCs in 1994.

11.2 Known Problems with the Data

Missing data with TDL-TGAS are associated with vibration problems, analysis of REA samples, and, for IFC-1, pump troubleshooting.

11.3 Usage Guidance

None given.

11.4 Other Relevant Information

None given.

12. Application of the Data Set

These data are useful for the study of water, energy, carbon, and nitrogen exchange in a mature black spruce forest.

13. Future Modifications and Plans

None.

14. Software

14.1 Software Description

None given.

14.2 Software Access

None.

15. Data Access

The SSA-OBS tower flux and meteorological data are available from the Earth Observing System Data and Information System (EOSDIS) Oak Ridge National Laboratory (ORNL) Distributed Active Archive Center (DAAC).

15.1 Contact Information

For BOREAS data and documentation please contact:

ORNL DAAC User Services
Oak Ridge National Laboratory
P.O. Box 2008 MS-6407
Oak Ridge, TN 37831-6407

Phone: (423) 241-3952 Fax: (423) 574-4665

E-mail: ornldaac@ornl.gov or ornl@eos.nasa.gov

15.2 Data Center Identification

Earth Observing System Data and Information System (EOSDIS) Oak Ridge National Laboratory (ORNL) Distributed Active Archive Center (DAAC) for Biogeochemical Dynamics http://www-eosdis.ornl.gov/.

15.3 Procedures for Obtaining Data

Users may obtain data directly through the ORNL DAAC online search and order system [http://www-eosdis.ornl.gov/] and the anonymous FTP site [ftp://www-eosdis.ornl.gov/data/] or by contacting User Services by electronic mail, telephone, fax, letter, or personal visit using the contact information in Section 15.1.

15.4 Data Center Status/Plans

The ORNL DAAC is the primary source for BOREAS field measurement, image, GIS, and hardcopy data products. The BOREAS CD-ROM and data referenced or listed in inventories on the CD-ROM are available from the ORNL DAAC.

16. Output Products and Availability

16.1 Tape Products

None.

16.2 Film Products

None.

16.3 Other Products

These data are available on the BOREAS CD-ROM series.

17. References

17.1 Platform/Sensor/Instrument/Data Processing Documentation None given.

17.2 Journal Articles and Study Reports

Businger, J.A. 1986. Evaluation of the accuracy with which dry deposition can be measured with current micrometeorological techniques. J. Clim. and Appl. Meteorol. 25:1100-1124.

Businger, J.A. and S.P. Oncley. 1990. Flux measurement with conditional sampling. J. Atmos. Ocean. Tech., 7: 349-352.

Chahuneau, F., R.L. Desjardins, E.J. Brach, and R. Verdon. 1989. A micrometeorological facility for eddy flux measurements of CO₂ and H₂O. J. Clim. Appl. Meteorol. 25: 1100-1124.

Desjardins, R.L., J.I. MacPherson, L. Mahrt, P. Schuepp, E. Pattey, H. Neumann, D. Baldocchi, S. Wofsy, D. Fitzjarrald, H. McCaughey, and D.W. Joiner. 1997. Scaling up flux measurements for the boreal forest using aircraft-tower combinations. Journal of Geophysical Research 102(D24):29,125-29,133.

Desjardins, R.L., P. Rochette, J.I. MacPherson, and E. Pattey. 1992. Measurements of greenhouse gas fluxes using aircraft- and tower-based techniques. In "Agricultural Ecosystem Effects on Trace Gases and Global Climate Change" ASA special publication #55: 45-62.

Horst, T.W. and J.C. Weil. 1992. Footprint estimation for scalar flux measurements in the atmospheric surface layer. Boundary-Layer Meteorol., 59: 279-296.

Newcomer, J., D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers, eds. 2000. Collected Data of The Boreal Ecosystem-Atmosphere Study. NASA. CD-ROM.

Pattey, E., R.L. Desjardins, and G. St-Amour. 1997. Mass and energy exchanges over a black spruce forest during key periods of BOREAS 1994. Journal of Geophysical Research, 102(D24):28,967-28,976.

Pattey, E., R.L. Desjardins, and P. Rochette. 1993. Accuracy of the relaxed eddy-accumulation technique, evaluated using CO₂ flux measurements. Boundary-Layer Meteorol., 66: 341-355.

Pattey, E., R.L. Desjardins, F. Boudreau, and P. Rochette. 1992. Impact of density fluctuations on flux measurements of trace gases: implications for the relaxed eddy accumulation technique. Boundary-Layer Meteorol., 59: 195-203.

Pattey, E., W.G. Royds, R.L. Desjardins, D.J. Buckley and P. Rochette. 1995. Software description of a data acquisition and control system for measuring trace gas and energy fluxes by eddy-accumulation and correlation techniques. Computers and Electronics in Agriculture (submitted for publication).

Scheupp, P.H., M.Y. Leclerc, J.I. Macpherson, and R.L. Desjardins. 1990. Footprint prediction of scalar fluxes from analytical solutions of the diffusion equation. Bound. Layer Meteorol., 50:355-373.

Schotanus, P., F.T.M. Nieuwstadt, and H.A.R. de Bruin. 1983. Temperature measurement with a sonic anemometer and its application to heat and moisture fluxes. Bound. Layer Meteorol., 26:81-93.

Sellers, P. and F. Hall. 1994. Boreal Ecosystem-Atmosphere Study: Experiment Plan. Version 1994-3.0, NASA BOREAS Report (EXPLAN 94).

Sellers, P. and F. Hall. 1996. Boreal Ecosystem-Atmosphere Study: Experiment Plan. Version 1996-2.0, NASA BOREAS Report (EXPLAN 96).

Sellers, P., F. Hall, and K.F. Huemmrich. 1996. Boreal Ecosystem-Atmosphere Study: 1994 Operations. NASA BOREAS Report (OPS DOC 94).

Sellers, P., F. Hall, and K.F. Huemmrich. 1997. Boreal Ecosystem-Atmosphere Study: 1996 Operations. NASA BOREAS Report (OPS DOC 96).

Sellers, P., F. Hall, H. Margolis, B. Kelly, D. Baldocchi, G. den Hartog, J. Cihlar, M.G. Ryan, B. Goodison, P. Crill, K.J. Ranson, D. Lettenmaier, and D.E. Wickland. 1995. The boreal ecosystem-atmosphere study (BOREAS): an overview and early results from the 1994 field year. Bulletin of the American Meteorological Society. 76(9):1549-1577.

Sellers, P.J., F.G. Hall, R.D. Kelly, A. Black, D. Baldocchi, J. Berry, M. Ryan, K.J. Ranson, P.M. Crill, D.P. Lettenmaier, H. Margolis, J. Cihlar, J. Newcomer, D. Fitzjarrald, P.G. Jarvis, S.T. Gower, D. Halliwell, D. Williams, B. Goodison, D.E. Wickland, and F.E. Guertin. 1997. BOREAS in 1997: Experiment Overview, Scientific Results and Future Directions. Journal of Geophysical Research 102(D24): 28,731-28,770.

Webb, E.K., G.I. Pearman, and R. Leuning. 1980. Correction of flux measurements density effects due to heat and water vapour transfer. Quart. J. R. Met. Soc. 106:85-100.

17.3 Archive/DBMS Usage Documentation None.

18. Glossary of Terms

None.

19. List of Acronyms

A/D - Analog to Digital - Aerodynamic Gradient AG

ASCII - American Standard Code for Information Interchange

BOREAS - BOReal Ecosystem-Atmosphere Study

BORIS - BOREAS Information System CD-ROM - Compact Disk-Read-Only Memory DAAC - Distributed Active Archive Center

EC - Eddy Covariance
EOS - Earth Observing System

EOSDIS - EOS Data and Information System GIS - Geographic Information System

GMT - Greenwich Mean Time

GSFC - Goddard Space Flight Center HTML - HyperText Markup Language IFC - Intensive Field Campaign IRGA - Infrared Gas Analyzer

NAD83 - North American Datum of 1983

NASA - National Aeronautics and Space Administration

NSA - Northern Study Area OBS - Old Black Spruce

ORNL - Oak Ridge National Laboratory PANP - Prince Albert National Park

PAR - Photosynthetically Active Radiation PC - Personal Computer

PPFD - Photosynthetic Photon Flux Density

REA - Relaxed Eddy Accumulation

REBS - Radiation Energy Balance Systems

SSA - Southern Study Area
TDL - Tunable-Diode Laser

TF - Tower Flux

TGA - Trace Gas Analyzer
TGB - Trace Gas Biogeochemistry TGAS - Trace Gas Analyzer System URL - Uniform Resource Locator

WAB - Wind Aligned Blob
WMO - World Meteorological Organization

20. Document Information

20.1 Document Revision Date

Written: 04-Oct-1995 Revised: 24-Sep-1999

20.2 Document Review Date(s)

BORIS Review: 08-Apr-1999

Science Review:

20.3 Document ID

20.4 Citation

When using these data, please include the following acknowledgment as well as citations of relevant papers in Section 17.2:

These data were provided by Drs. E. Pattey and R.L. Desjardins. This work was supported by Agriculture and Agri-Food Canada.

If using data from the BOREAS CD-ROM series, also reference the data as:

Desjardins, R.L. and E. Pattey, "Areal Estimates of Mass and Energy from a Boreal Forest Biome." In Collected Data of The Boreal Ecosystem-Atmosphere Study. Eds. J. Newcomer, D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers. CD-ROM. NASA, 2000.

Also, cite the BOREAS CD-ROM set as:

Newcomer, J., D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers, eds. Collected Data of The Boreal Ecosystem-Atmosphere Study. NASA. CD-ROM. NASA, 2000.

20.5 Document Curator

20.6 Document URL

REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arignoton, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

Davis Highway, Suite 1204, Arlington, VA 22202-43				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE November 2000	3. REPORT TYPE AND DATES COVERED Technical Memorandum		
4. TITLE AND SUBTITLE	11010111001 2000	Techni	5. FUNDING NUMBERS	
Technical Report Series on the Bo	oreal Ecosystem-Atmosphere	Study (BOREAS)	3. I ONDING NOMBERG	
BOREAS TF-7 SSA-OBS To	•	• ` ` '	923	
	wei i iux and wieteorolog	gicai Data	RTOP: 923-462-33-01	
6. AUTHOR(S)			RTOP: 923-402-33-01	
Elizabeth Pattey and Raymon	J			
Forrest G. Hall and Karl Hue	mmrich, Editors			
7. PERFORMING ORGANIZATION NAME	E(S) AND ADDRESS (ES)		8. PEFORMING ORGANIZATION REPORT NUMBER	
Goddard Space Flight Center			KEI OKI NOMBEK	
Greenbelt, Maryland 20771			2000-03136-0	
9. SPONSORING / MONITORING AGE	ENCY NAME(S) AND ADDRESS	(ES)	10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
National Aeronautics and Space	Administration		TM-2000-209891	
Washington, DC 20546-0001			Vol. 202	
Ç ,				
11. SUPPLEMENTARY NOTES				
E. Pattey and R.L. Desjardins	· Agriculture and Agri-Fo	ood Canada Ottav	va Ontario:	
K. Huemmrich: University of	0	*		
•	<u> </u>	ard Space I fight C	•	
12a. DISTRIBUTION / AVAILABILITY STA	ATEMENT		12b. DISTRIBUTION CODE	
Unclassified-Unlimited				
Subject Category: 43				
Report available from the NASA	*	·		
7121 Standard Drive, Hanover,	MD 21076-1320. (301) 62	1-0390.		
13. ABSTRACT (Maximum 200 words)				
The BOREAS TF-7 team coll	lected meteorological dat	a as well as energy	y, carbon dioxide, water vapor,	

The BOREAS TF-7 team collected meteorological data as well as energy, carbon dioxide, water vapor, methane, and nitrous oxide flux data at the BOREAS SSA-OBS site. The data were collected from 24-May to 19-Sep-1994. The data are available in tabular ASCII files.

14. SUBJECT TERMS BOREAS, tower flux, meteorological data.			15. NUMBER OF PAGES 20 16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UL	